Product Specifications





1375189-1

SL110 Series Modular Jack, category 5e, T568A/T568B, shielded, 180° (rear) entry shield, black

Product Classification

Portfolio	NETCONNECT®
Product Series	SL Series
Product Type	Modular jack
Regional Availability	Asia EMEA Latin America North America

Body Features

110 Block Material	Polycarbonate
Cover Material	Polycarbonate
Shield Material	Copper zinc alloy

Configuration Features

Keyed	No
Number of Positions	8
Wiring Pattern	Universal

Contact Features

Contact Base Material	Beryllium copper		
Contact Mating Area Plating Material	Gold		
Contact Mating Area Plating Thickness	50.00 µin		1.27 µm

Dimensions

Insulated Conductor Outside Diamete	r 0.057 in 1.45 mm
Solid Wire Range	24 – 22 AWG
Stranded Wire Range	26 – 24 AWG

Housing Features

Housing Color	Black
Housing Material	Polyphenylene Oxide (PPO)

Industry Standards

UL Flammability Rating

UL 94V-0

Mechanical Attachment

©2018 CommScope, Inc. All rights reserved. All trademarks identified by ® or ™ are registered trademarks, respectively, of CommScope. All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: January 17, 2018

Product Specifications



1375189-1

Mounting Type	Panel Mount
Packaging Features	
Packaging Method	Poly Bag
Packaging Quantity	1
Product Type Features	
Performance Category	Category 5e
Shielded	Yes
Connector Type	Connector Assembly
Dust Cover	Without
Jack Type	RJ45
Termination Features	
Termination Method to Wire/Cable	Insulation Displacement Crimp (IDC)
Termination Style	SL Termination Tool
Regulatory Compliance/Certifications	

Agency RoHS 2011/65/EU **Classification** Compliant