



1375192-1

**SL110 Series Modular Jack, 8-position, RJ11, category 3, unshielded, without dust cover, almond**

## Product Classification

Portfolio	NETCONNECT®
Product Series	SL Series
Product Type	Modular jack
Regional Availability	Asia   Australia/New Zealand   EMEA   Latin America   North America

## Body Features

110 Block Material	Polycarbonate
--------------------	---------------

## Configuration Features

Keyed	No
Number of Positions	6
Wiring Pattern	Universal

## Contact Features

Contact Base Material	Beryllium copper
Contact Mating Area Plating Material	Gold
Contact Mating Area Plating Thickness	50.00 µin   1.27 µm

## Dimensions

Insulated Conductor Outside Diameter	0.057 in   1.45 mm
Solid Wire Range	.51 mm <sup>2</sup>   .65 mm <sup>2</sup>
Stranded Wire Range	.14 mm <sup>2</sup>   .2 mm <sup>2</sup>
Wire Range	22 AWG   24 AWG   26 AWG

## Housing Features

Housing Color	Almond
Housing Material	Polycarbonate

## Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------

## Mechanical Attachment

1375192-1

Mounting Type SL Series Faceplate

## Other

Comment With strain relief.

## Packaging Features

Packaging Method Poly Bag  
Packaging Quantity 1

## Product Type Features

Performance Category Category 3  
Shielded No  
Applies To Panel  
Cable Type Unshielded Twisted Pair  
Connector Type Connector Assembly  
Dust Cover Without  
Jack Type RJ11

## Termination Features

Termination Method to Wire/Cable Insulation Displacement Crimp (IDC)  
Termination Style SL Termination Tool

## Regulatory Compliance/Certifications

**Agency**  
RoHS 2011/65/EU

**Classification**  
Compliant