

Fiber Optic Patch Cord, Duplex, Multimode, LC/UPC to SC/UPC, Aqua

Product Classification

Regional Availability

Asia | Australia/New Zealand | China | India

Portfolio CommScope®

Product Type Fiber patch cord, duplex

General Specifications

Color, boot ABlueColor, boot BBlueColor, connector ABeigeColor, connector BBeigeConnector A, quantity2Connector B, quantity2

 Interface, Connector A
 LC/UPC

 Interface, Connector B
 SC/UPC

 Jacket Color
 Aqua


Polarity Pairs, flipped

Dimensions

Diameter Over Jacket 1.8 mm | 0.071 in

Ordering Tree





Optical Specifications

Fiber Mode Multimode

Fiber Type OM3, LazrSPEED®

Insertion Loss, maximum, connector A0.15 dBInsertion Loss, maximum, connector B0.15 dBReturn Loss, minimum, connector A35 dBReturn Loss, minimum, connector B35 dB

Environmental Specifications

Operating Temperature -10 °C to +60 °C (+14 °F to +140 °F)

Environmental Space Low Smoke Zero Halogen (LSZH)

Qualification Standards IEC 60332-1 | IEC 60332-3 | IEC 60754 | IEC 61034

Packaging and Weights

Packaging quantity 1

