

Bảng thông số sản phẩm

Thông số kỹ thuật



APC Easy UPS On-Line SRV 3000VA 230V with Extended Runtime Battery Pack

SRV3KIL

Overview

Presentation High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.

Lead time Usually in Stock

Main

Main Input Voltage 230 V

Other Input Voltage 220 V
240 V

Main Output Voltage 230 V

Other Output Voltage 220 V
240 V

Rated power in W 2400 W

Rated power in VA 3000 VA

Plug standard IEC 60320 C14

Nb of power socket outlets 6 IEC 60320 C13
1 IEC 60320 C19

Cable length 1.52 m

Number of cables 1

Provided equipment Basic UPS signalling RS-232 cable
CD with software
Country-specific detachable power cord
1 x DC cable
User manual
USB cable

General

Number of power module filled slots 0

Number of power module free slots 0

Redundant No

Physical

Colour Black

Height 33.6 cm

Width 42.5 cm

Depth	42.5 cm
Net weight	45.9 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Not rack-mountable
USB compatible	Yes
Mounting position	Vertical

Input

Input voltage limits	110...285 V half load 160...280 V full load
Network frequency	40...70 Hz auto sensing

Output

Maximum configurable power in VA	3000 VA
Maximum configurable power in W	2400 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Harmonic distortion	3 %
Transfer time	4 ms typical
UPS type	Double conversion online
Wave type	Sine wave
Efficiency	88 % (full load)
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Bypass type	Internal bypass (automatic and manual)
Crest factor	3 : 1

Conformance

Product certifications	CE EAC TISI
Standards	EN/IEC 62040-1 EN/IEC 62040-2

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m
Ambient air temperature for storage	-20...50 °C
Storage Relative Humidity	Non-condensing 0...95 %
Storage altitude	0...15000 m
Acoustic level	50 dBA
Heat dissipation	910 Btu/h
IP degree of protection	IP20

Batteries & Runtime

Battery type	Lead-acid battery
Battery voltage	72 V
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	5.5 h
Battery life	3...5 year(s)
Battery charger power	350 W rated
Battery option	SRV72BP-9A 1 1878 VAh SRV72BP-9A 2 2817 VAh SRV72BP-9A 3 3756 VAh SRV72BP-9A 4 4695 VAh

Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Control panel	Multifunction LCD status and control console
Free slots	1

Surge Protection and Filtering

Surge energy rate	600 J
-------------------	-------

Packing Units

Package 1 Weight	49.8 kg
Package 1 Height	46.5 cm
Package 1 width	56.5 cm
Package 1 Length	56.5 cm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Under investigation

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------