

# Bảng thông số sản phẩm

Thông số kỹ thuật



## Power Cord Kit (6 ea), Locking, C13 to C14, 1.8m

AP8706S-WW

### Overview

**Presentation** This Series of Rack Power Distribution Units (PDU) comes with Locking IEC Receptacles. The output and input connections are C13 to C14. The cord length is 1.8m. Locking IEC system allows the use of optional locking IEC power cords for added power cord security and enhanced reliability. No tools are required to disengage the locking feature and remove the plug from the locking receptacle.

**Lead time** Usually in Stock

### Main

**Plug standard** IEC 60320 C14

**Cable length** 1.83 m

**Number of cables** 6

### Physical

**Colour** Black

**Height** 24 cm

**Width** 7.5 cm

**Depth** 5.5 cm

**Product weight** 1.35 kg

**Mounting preference** No preference

**Mounting mode** Not rack-mountable

### Input

**Max line current** 10 A

**Input current limits** 10 A

### Output

**Max current draw** 10 A

**Number of power socket outlets** 1 IEC 60320 C13

**Power cable length** 1.83 m

### Conformance

**Product certifications** CCC  
PSE  
VDE

## Environmental

Ambient air temperature for operation	0...70 °C
Relative humidity	20...80 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...75 °C
Storage Relative Humidity	20...80 %
Storage altitude	0.00...15240.00 m

## Packing Units

Package 1 Weight	1.35 kg
Package 1 Height	24 cm
Package 1 width	7.5 cm
Package 1 Length	5.5 cm
Number of Units in Package 3	300

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Lead free	Yes
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	Take-back program available

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------