

# Bảng thông số sản phẩm

Thông số kỹ thuật



## Power Cord Kit (6 ea), Locking, C19 to C20 (90 Degree), 1.2m

AP8714R

### Overview

**Presentation** Free up space and secure power cords between rack-mount PDUs and attached IT equipment with this exclusive easy-to-use cord retention method. While these cords will fit into any standard IEC receptacle or power inlet; the "locking" feature is enabled only when used with APC AP8000 series Rack PDUs or IT equipment with built-in locking receptacles. These locking connectors reduce the probability of accidentally disconnecting cords and dropping loads.

**Lead time** Usually in Stock

### Main

**Plug standard** IEC 60320 C20

**Cable length** 1.22 m

**Number of cables** 6

**Provided equipment** 3 left-angle jumper cords  
3 right-angle jumper cords

### Physical

**Colour** Black

**Height** 30 cm

**Width** 6.5 cm

**Depth** 7 cm

**Product weight** 1.64 kg

**Mounting preference** No preference

**Mounting mode** Not rack-mountable

### Input

**Max line current** 16 A

**Input current limits** 16 A

### Output

**Max current draw** 16 A

**Number of power socket outlets** 1 IEC 60320 C19

**Power cable length** 1.22 m

## Conformance

Product certifications	CCC CSA PSE UL listed VDE
------------------------	---------------------------------------

## Environmental

Ambient air temperature for operation	0...75 °C
Relative humidity	20...80 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...75 °C
Storage Relative Humidity	20...80 %
Storage altitude	0.00...15240.00 m

## Packing Units

Package 1 Weight	1.64 kg
Package 1 Height	30 cm
Package 1 width	6.5 cm
Package 1 Length	7 cm
SCC14	10731304279690
Number of Units in Package 3	270

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Lead free	Yes
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	Take-back program available

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------