

Bảng thông số sản phẩm

Thông số kỹ thuật



Power Cord Kit (6 ea), Locking, C19 to C20, 1.2m

AP8714S

Overview

Presentation	Free up space and secure power cords between rack-mount PDUs and attached IT equipment with this exclusive easy-to-use cord retention method. While these cords will fit into any standard IEC receptacle or power inlet; the "locking" feature is enabled only when used with APC AP8000 series Rack PDUs or IT equipment with built-in locking receptacles. These locking connectors reduce the probability of accidentally disconnecting cords and dropping loads.
---------------------	---

Lead time	Usually in Stock
------------------	------------------

Main

Plug standard	IEC 60320 C20
----------------------	---------------

Cable length	1.22 m
---------------------	--------

Number of cables	6
-------------------------	---

Physical

Colour	Black
---------------	-------

Height	30 cm
---------------	-------

Width	7 cm
--------------	------

Depth	7 cm
--------------	------

Product weight	1.64 kg
-----------------------	---------

Mounting preference	No preference
----------------------------	---------------

Mounting mode	Not rack-mountable
----------------------	--------------------

Input

Max line current	16 A
-------------------------	------

Input current limits	16 A
-----------------------------	------

Output

Max current draw	16 A
-------------------------	------

Number of power socket outlets	1 IEC 60320 C19
---------------------------------------	-----------------

Power cable length	1.22 m
---------------------------	--------

Conformance

Product certifications	CCC CSA PSE
-------------------------------	-------------------

UL listed
VDE

Environmental

Ambient air temperature for operation	0...75 °C
Relative humidity	20...80 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...75 °C
Storage Relative Humidity	20...80 %
Storage altitude	0.00...15240.00 m

Packing Units

Package 1 Weight	1.64 kg
Package 1 Height	30 cm
Package 1 width	7 cm
Package 1 Length	7 cm
SCC14	10731304279706
Number of Units in Package 3	270

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------
